WAVE PROPULSION DEVICE

Patent Number:

CA2245286

Publication date:

2000-03-04

Inventor(s):

MANCUSO ROBERT BRIAN (CA)

Applicant(s):

MANCUSO ROBERT BRIAN (CA)

Requested Patent:

□ CA2245286

Application Number: CA19982245286 19980904

Priority Number(s): CA19982245286 19980904

IPC Classification:

B63H1/37; B64C11/00; F03B13/14; B63H1/14; A01K85/14

EC Classification:

A01K85/18, B63H1/36, B63H19/02

Equivalents:

Abstract

An externally powered propulsion device particularity designed to propel floating and submerged water craft, as well as any other vehicles (land or air). The device utilizes a helical coil drive mechanism which causes a flexible body plate(s) to move and undulate in such a way that a travelling unilineal wave motion is produced. The resulting wave creates thrust within any fluidic medium. (See attached description for more detailed information.) In brief, the device is designed to transform mechanical standing wave motion into a travelling wave pattern applicable as a propulsion mechanism. The device is also broadly applicable in many situations where a travelling wave pattern may be desirable for reasons not related to vehicular propulsion (e.g., pumps, fans, fishing lures, massaging devices, conveyers, amusement devices, etc.).

Data supplied from the esp@cenet database - I2

Best Available Copy

12

EUROPEAN PATENT APPLICATION

2 Application number: 87306034.7

2 Date of filing: 08.07.87

(9) Int. Cl.4: **B 63 H 19/02** B 63 H 1/36

30 Priority: 08.07.86 CA 513352

43 Date of publication of application: 13.01.88 Bulletin 88/02

Designated Contracting States:
AT BE CH DE ES FR GB GR IT LI LU NL SE


(7) Applicant: Momot, Adam 2-335 West 15th Avenue Vancouver British Columbia, V5Y 1Y3 (CA)

inventor: Momot, Adam 2-335 West 15th Avenue Vancouver British Columbia, V5Y 1Y3 (CA)

(3) Representative: Parry, Christopher Stephen et al Page White & Farrer 5 Plough Place New Fetter Lane London EC4A 1HY (GB)

(a) A propulsion system for a water borne vessel.

(g) A propulsion system for a water-borne vessel (11). There is a generally inflexible fin member (13). An inflexible projection member (10) is connected to the vessel. It has resilient connecting means (12) attached to the generally inflexible fin member (13). The inflexible projection member is connected to the vessel so as to be held below water along an axis parallel to the water line.



Hydrodynamic ship propulsion

Patent Number:

DE3303535

Publication date:

1984-08-09

Inventor(s):

MENZEL JOACHIM (DE)

Applicant(s):

MENZEL JOACHIM

Requested Patent:

□ DE3303535

Application Number: DE19833303535 19830203

Priority Number(s):

DE19833303535 19830203

IPC Classification:

B63H19/02; B63H1/36

EC Classification:

B63H1/36, B63H19/02

Equivalents:

Abstract

For the propulsion of a ship, the sea waves can also be used in addition to wind and power propulsion. This force is transmitted to the ship by the hydrodynamic drive in that two surfaces movably arranged in relation to one another alternately generate overpressure and underpressure.

Data supplied from the esp@cenet database - I2

Best Available Copy

A rudder

Patent Number:

☐: GB2326143

Publication date:

1998-12-16

Inventor(s):

COSTELLO PADRAIC

Applicant(s):

COSTELLO PADRAIC (IE)

Requested Patent:

厂 CA2245233

Application Number: GB19980004100 19980226

Priority Number(s):

CA19982245233 19980818; IE19970000113 19970226

IPC Classification:

B63H25/38; B63H1/36

EC Classification:

B63H25/38M, B63H1/36, B63H16/08

Equivalents:

Abstract

A rudder (40) has a rudder blade (41) mounted on a tiller stock (42) which is pivoted by a tiller (43). The tiller stock (42) is rotatably mounted on a mounting plate (45) which is engagable with a transom on a boat to mount the rudder (40) on the boat. The rudder (40) has a flexible drive fin (47) an inner end of which is clamped between a pair of metal plates (50) attached to the tiller stock (42). A free outer end of the drive fin (47) has a fish tail shape. An inner end of the rudder is rigid to provide steering like a conventional rudder while the outer end flexes back and forth like a fish tail if the tiller is moved back and forth to provide propulsion to drive the boat through the water.

Data supplied from the esp@cenet database - I2